

What is claimed is:

1. An optical element, comprising:
 - a base material; and
 - a layer formed on at least one of surfaces of the base material;wherein a reflectance of a surface of the formed layer for all light rays in a wavelength region of 280 nm to 315 nm and in a wavelength region of 420 nm to 680 nm is smaller than a reflectance of a surface of the base material.
2. The optical element of claim 1, wherein the layer is made of substantially an inorganic material.
3. The optical element of claim 1, wherein a surface resistance of the layer is $1 \text{ M}\Omega/\text{cm}^2$ or less.
4. The optical element of claim 1, wherein the base material is a lens and the layer is formed on an image side-entire surface of the lens.
an eye side-entire surface of the lens.

6. The optical element of claim 1, wherein a reflectance of a surface of the formed layer for all light rays in a wavelength region of 280 nm to 400 nm and in a wavelength region of 420 nm to 680 nm is smaller than a reflectance of a surface of the base material.
7. The optical element of claim 1, wherein a reflectance of a surface of the formed layer for all light rays in a wavelength region of 280 nm to 700 nm is smaller than a reflectance of a surface of the base material.
8. The optical element of claim 1, wherein a absorptivity of the base material for at least a part of light rays in a wavelength of 280 nm to 400 nm is 30% or more.
9. The optical element of claim 1, wherein the base material has a selective absorptivity to absorb selectively a part of light rays in a wavelength region of 400 to 700 nm.
10. The optical element of claim 1, wherein the layer is a

11. The optical element of claim 1, wherein the layer comprises a transparent conductive layer.
12. The optical element of claim 1, wherein the transparent conductive layer contains indium oxide.
13. The optical element of claim 1, wherein the layer comprises a metallic layer.
14. The optical element of claim 1, wherein a luminous transmittance of the layer is 90% or more.
15. The optical element of claim 1, wherein a luminous transmittance of the base material and the layer is 75% or less.
16. The optical element of claim 1, wherein a difference between a luminous reflectance one surface and a luminous reflectance on the other one surface of the optical element is 1% or less.

16.1. If 40 nm to 110 nm is 90% or more.

18. The optical element of claim 1, wherein
the base material is a lens,
the layer is formed on an image side surface of the
base material and
another layer is formed on an object side surface of
the base material, and
wherein a difference between a wavelength showing a peak of a
spectral reflectance on the image side surface and a
wavelength showing a peak of a spectral reflectance on the
object side surface in a wavelength region of 450 nm to 680
nm is $\pm 5\%$ or less and a difference between a peak reflectance
on the image side surface and a peak reflectance on the
object side surface in a wavelength region of 450 nm to 680
nm is 1% or less.

19. An eyeglass, comprising:
a lens comprising
a base material, and
a layer formed on at least one of surfaces of the
base material; and

for all light rays in at least one of a wavelength region of

280 nm to 315 nm and in a wavelength region of 420 nm to 680 nm is smaller than a reflectance of a surface of the base material.

20. The eyeglass of claim 19, wherein the layer is formed on an eye side-entire surface of the base material.